




Setting 65,75,85 °C Easy for Tea, Coffee, Milk or Noodle!

\* Press and hold for 3 seconds to enter setup mode.







Model: TPH-1539SBW

Touch Panel Faucet or Mechanical Type

Size: W145 x D300 x H390mm

Service: Hot/Ambient Water Hot Water Consumption: 750W

Capacity: Hot 3L Install Hole: 30mm

#### Safety Secure:

- · Leakage circuit breaker
- · Overload protection fuse

Voltage: 110V or 220V, Separately power supply



### **TPH-1539SBW**



# **Touch Panel Faucet with Under-sink Water Dispenser**





**BLUE** AMBIENT

## **LED lights**

Intuitive Color Matching - Indicate the water dispensing status.



The temperature displayed in this catalog is for reference only. Please refer to the actual temperature inside the heating tank as the standard.

### **Compact Size**

Saving Space Good choice for Hot Water Service.



#### **Touch Panel Faucet**

Dual Safety Sesign -Anti-scalding insulation and Automatic power cutoff.











\*\*Unlike Traditional Heating Tubes on the Market.

# **Seamless Stainless Steel Heating Tube**

- **✓** 100% Lead-Free!
- **✓** Fast Heating Efficiency!
- ✓ No Tube Burst Even Under Overheating!

H-1539W



# Mechanical Faucet with Under-sink Water Dispenser



Model: H-1539W (Mechanical)
Stainless Steel Faucet (Optional)
Size: W145 x D300 x H390mm
Service: Hot/Ambient Water
Hot Water Consumption: 750W

Capacity: Hot 3L

Safety Secure:

- · Leakage circuit breaker
- · Overload protection fuse Voltage: 110V or 220V,

Separately power supply Install Hole: 30mm

#### Hot Water Service

Pull out the handle and turn counterclockwise



**Ambient Service** 

Turn the handle clockwise



www.puretron.com.tw

TEL: +886 4-25311188 FAX: +886 4-25310606 sales@triwin.com.tw